

THE PORTABLE MOISTURE ANALYZER FOR HAY, STRAW AND SILAGE

SUPERPRO COMBI



Superpro Combi is a new generation of reliable moisture meters for hay, straw and silage

Superpro Combi enables you to read actual moisture in the bale, average the moisture content, display the number of stored measurements and read bale temperature. This device stores each measurement to memory and automatically calculates the average moisture content, thereby giving higher accuracy than other moisture meters.

Key features and benefits

- Easy to use and operate
- Automatic temperature compensation
- Calculation of average value up to 99 bales
- Adjustment of calibrations to compensate for bale density variation
- Back light display for easy reading
- Two-year warranty

Reliable measurement requires multiple readings in the bale due to density variation. This ensures a valid average moisture level.



FUNCTIONS

Superpro Combi

Easy to use and handle



① Turn on the tester by pressing the ON button.

② Stick the stainless steel probe into the bale.

③ Read the moisture content directly from the display.

④ Press the memory button to save measurement and automatically calculate average moisture content.

TECHNICAL SPECIFICATIONS

Measuring range (Moisture): 8.5 to 80%
Operating range (Temperature): 0 to 70 °C
Resolution: 0.1% moisture
Probe: 50 cm stainless steel

Battery: 9 V Alkaline
Display: 2 line LCD with backlight
Accuracy: Better than +/- 1.5% In normal moisture range when using average and calibration adjustments

AgroLog App

With the AgroLog App you are always in control of your products and storage, you get real-time insights and a historical overview of your crops.

There is a complete overview of the data collected from all devices at different times. All this information is available in the app and accessible through your smartphone.



Multiple products

Simple overview

Traceability

Customization



Download the app here



Supertech Agroline ApS
 Maltgoerervej 7
 5471 Soendersee, Denmark

Phone: +45 6481 2000
 Email: info@supertech.dk
 www.supertechagroline.com